





DESIGN <i>[Signature]</i>	DRAWN BY <i>[Signature]</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>[Signature]</i>	APPROVED <i>[Signature]</i>	DRAWING NO. D2735	REV. C SHEET 1 OF 2
DATE 98.12.14		TITLE LUG BRACKET	SCALE 2:3
A	97.12.14	NEW ISSUE	
B	98.10.23	UPDATE MATERIAL (TSR A1114)	
C	98.12.14	REMOVE TOOLING HOLES (TSR A1040)	


RELEASED
98.12.14 DS




D2735-1 FLAT PATTERN
SYMMETRIC ABOUT BOTH CENTRE-LINES (CL)



D2735-3 FLAT PATTERN
SYMMETRIC ABOUT CENTRE-LINE (CL)



RELEASED
98.12.14 DS



D2735-1 AND D2735-3 SHOULD BE BENT TO WITHIN 0.010 OF THE OUTSIDE PROFILE OF THE D2500-1 EXTRUSION IN THE AREAS INDICATED 'X' ABOVE.

MATERIAL: ASTM A36/A366/A569/A570 OR AISI 1010-1025 STEEL
0.125 THICK (11 GAUGE)
MIN. ULTIMATE TENSILE STRENGTH = 42 ksi
MIN. YIELD TENSILE STRENGTH = 28 ksi

TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
ALL DIMENSIONS ARE IN INCHES